

Technical Data Sheet

General Description

Glass fiber wall covering is used to cover walls and other interior surfaces. Product is perfect for new spaces: thanks to its high mechanical properties it prevents cracks from appearing, consequently prolonging the surface lifetime. It is also a performing solution for light renovation: it covers crack and wall irregularities.

Product from Novelio® Nature range is perfect solution for easy application without important preparation of the wall surface and highly decorative expectations. This range mimics natural wall coverings and products do not need to be painted.

Technical characteristics

Technical Characteristics	
Composition	100 % coated glass fiber
Treated fabric weight (average value)	200 g / m ² (± 8 %)
Oekotex certificate Standard 100	Product Class III
Emission in indoor air	A+ (very low)
Fire resistance (EN 13501-1)	Euroclass B-s 1,d 0
Recommendation for application	
Quantity of vinyl glue	250 g / m ² (approximate)
Dimensions & Packaging	
Width (individual value)	49 cm (± 1 % or closed pattern repeat)
Roll length (individual value) ⁽¹⁾	10.05 m (± 1 %)
Roll packaging ⁽²⁾	Plastic foil
Label on roll ⁽²⁾	With installation instructions
Storage conditions	Dry room, storing temperature from -10 °C to +50 °C. If product is not processed up to one week, it is not recommended to open a package or to remove a package from a roll.
Quality Control	
Traceability ⁽²⁾	Lot no. marked on the back side of the roll and on the small sticker on the roll
Defects marked by label ⁽²⁾	Maximum 3 point defects / 50m roll ⁽²⁾
Each defect is balanced by	Adding 50 cm / defect ⁽²⁾
Product is carefully checked before leaving the factory but should also be checked just before applying. Any claim should be accompanied with roll sticker and a sample featuring the defect.	

Properties

- Tear resistant
- High tensile strength
- Fire resistant
- Easily re-paintable
- Breathable
- PVC-free



Edited by:

ADFORS Construction Products Europe

SAINT-GOBAIN ADFORS CZ s.r.o.

Sokolovska 106

CZ – 570 01 Litomyšl

Tel: +420 461 651 111

Fax: +420 461 612 769

www.adfors.com

ADFORS reserves the right to change the information given herein without prior notice

Last update: 19/12/2017

⁽¹⁾ Other dimensions or features on request

⁽²⁾ Details are described in CAS 0337